

for ETICS made of expanded polystyrene (EPS) and rock wool (RW)

- suitable for screwing with wood or self-tapping screws
- Thickness: 10 mm



### Applications

- for installation in the insulating layer
- for mounting light loads, e.g. blind guide rails, lightweight signs or temperature sensors

### Processing

#### Notes

- Installation is carried out in accordance with the technical specifications of Dosteba GmbH, D-72770 Reutlingen-Betzlingen.

### Storage

- Store dry and as per instructions.

### Technical Data

#### Fire behaviour

E

All data are average values that were determined under laboratory conditions according to relevant test standards and application tests. Deviations are possible under practical conditions.

### Available articles

Product	Diameter	Usable area diameter
DoRondo®-PE 100	90 mm	70 mm
DoRondo®-PE 20	90 mm	70 mm

### General notes

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.