



## WALL AND FLOOR DESIGN

# NSTA Natural stone carpet sealing

sealing mortar and bonding bridge for quick-mix NST Natural stone carpet



### PROPERTIES

- good workability

### APPLICATIONS

- suitable for moist and wet rooms
- bonding bridge for non-absorbent substrates
- for walls and floors
- for interior and external use

### SUBSTRATE

The substrate must be dry, load-bearing, clean, dust-free and free of adhesion-reducing residues, release agents, efflorescence and sintered coatings.

In the case of non-absorbent substrates (e.g. tiles, smooth-formed concrete), scrape (scratch) the quick-mix natural stone carpet seal onto the substrate with the smoothing trowel, whereby a high adhesive bond is achieved. Pre-wet strongly absorbent substrates. Level uneven substrates beforehand.

### PROCESSING

The application as a seal is carried out in 2 layers with a wall brush or smoothing trowel. After the 1st layer has been applied, a drying time of at least 8 hours must be observed. The total layer thickness must not be less than 2 mm.

Allow the seal to dry for about 2 to 3 days before quick-mix natural stone carpet is applied. The fresh material must be protected against moisture until it is completely hardened. In the case of a non-absorbent substrate, scrape quickly-mix natural stone carpet seal on with the smoothing trowel (scratch filling) to create a contact layer. The scratch filling must be completely dry before the subsequent layer of quick-mix natural stone carpet seal is applied. Protect against moisture until then.

Clean all tools and equipment with water immediately after use.

Carefully cover adjacent surfaces and components (e.g. windows, window sills, etc.). Wash off contamination immediately with water.

### CONSUMPTION

consumption: 6 kg for approx. 1,75 m<sup>2</sup>

### STORAGE

Store dry and as per instructions.

### PACKAGING

- 6 kg/bag

### DISPOSAL

Due to the Green Dot, the empty packaging can be disposed of via the Dual System Germany.

### NOTE

The usual hygiene and precautionary measures when handling chemical products must be observed. Wear suitable protective clothing.



WALL AND FLOOR DESIGN

## NSTA Natural stone carpet sealing

sealing mortar and bonding bridge for quick-mix NST Natural stone carpet

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.

29.01.2023

**EMERGENCY NUMBER: +49 551 19 240**

quick-mix is a Sievert brand  
Sievert Baustoffe SE & Co. KG  
Mühlenschweg 6 • 49090 Osnabrück • Phone +49 541 601-01 • Fax +49 541 601-853 • [info@quick-mix.de](mailto:info@quick-mix.de) • [www.quick-mix.de](http://www.quick-mix.de)