

INTRASIT® SE-SL 18DD

Mould-Ex – repair solution for cleaning



These pictograms apply to the **basic product**.
Deviations are possible depending on the area of application and processing.

PRODUCT INFORMATION

Description

INTRASIT® SE-SL 18DD is an easy-to-use and ready-to-use cleaning liquid. Due to the use of special washing raw materials with fungicidal effect, a broad spectrum of action is possible.

Application

- as a component of the Mold-Ex remediation system for the effective removal of mold fungi or other microbial contamination such as green algae coatings

Operational area

- Green algae coatings on paved surfaces, facades, garden furniture, wet rooms, window sills, etc.
- Mold infestation on plaster, wallpaper, paint

Properties

- solvent-free
- ready-to-use
- not subject to labeling
- non bleaching
- chlorine-free
- acid-free

Technical Data

Available container sizes	5 kg/PE canister
Colour	transparent
pH value	approx. 7.5
Processing temperature	+5°C up to +35°C
Storage	frost-free and cool, 12 months
Consumption	approx. 0.1 – 0.2 kg/m ² depending on the absorbency of the substrate

AREAS OF APPLICATION AND PROCESSING



■ Applying

- INTRASIT® SE-SL 18DD is ready to use and can be painted, rolled or sprayed.
- After a reaction time of approx. 24 hours, any visible deposits can be removed mechanically, e.g. with a sponge or brush.

NOTES

■ Cleaning

- Clean tools immediately after use with water.

■ System products

- INTRASIT® RZ1 55HSP
- INTRASIT® RZ2 55HSP
- INTRASIT® SE-SB 10D
- INTRASIT® SE-SF 70A

■ To be observed

- Observe the relevant regulations for dealing with mold-contaminated surfaces, such as the “Guidelines for the search for causes and remediation of mold growth indoors (Federal Environment Agency)”, or the “Recommendations for the remediation of indoor areas infested with mold (Baden-Württemberg State Health Office)”
- Protect adjacent components from splashes and spray mist.

■ Ingredients

- 2.45 % quaternary ammonium compound
- < 5 % cationic surfactants

■ Occupational safety / Recommendation

- Avoid contact with the skin and inhalation of spray mist. Further information on safety during transportation, storage and handling can be found in the current safety data sheets. BAuA-reg. no. N-34505 liquid concentrate

■ Disposal

- The following applies to all systems: Only return empty containers to recycling partner Interseroh. Material residues can be disposed of according to waste directory regulations under Waste Code 07 04 01 (aqueous washing liquids and mother liquors).

■ Producer

Sievert Baustoffe SE & Co. KG
Mühlenschweg 6, 49090 Osnabrück
Tel. +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.