

akurit MPP

Mapapolk tape

PE-foam isolating tape

- self-adhesive
- tape thickness: 5 mm



Applications

- for elastic isolation of plaster and adjacent components
- for interior and external use

Properties

- good workability
- high bonding strength
- low thermal conductivity
- low water absorption
- high temperature resistance

Substrate

Condition / Testing

- The substrate must be dry, level, free of adhesion-reducing residues, dust and grease free as well as fit for the bonding.

Processing

Temperature

- Do not process or allow to dry out at air, material or substrate temperatures below +5°C, or if there is a risk of exposure to night frost, or at temperatures above +30°C, or in direct sunlight, or on heated up surfaces, and/or in windy conditions.

Applying / Processing / Assembling

- Before applying the base plaster, stick adhesive tape onto the adjacent building elements without tension in the width of the required base plaster thickness.
- If necessary, once the base plaster has hardened, cut off the protruding tape carefully with a sharp knife.
- If required, make a furrow in the plaster for separation purposes.

Notes

- Take subsequent coatings (finish coats, wallpapers, paint etc.) past the Mapapolk tape up to the adjacent building elements.

Packaging

- 10 m/roll

Storage

- Store dry and as per instructions.
- Protect against direct sunlight.

Quantity required / Yield

- consumption: approx. 1 m/m

akurit MPP

Mapapolk tape

General notes

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.