

floor edge insulating strips with integrated textile and self-adhesive base

- good sound absorption
- self-adhesive
- very good adhesion on clean substrates
- height: 50 mm



Applications

- for fixing onto rising components before applying strasser PLAN floor filler
- for use on raw concrete floors, screed, timber substrates etc.
- Prevents sound bridges and forced tensions in floor/wall connection joints
- for interior and external use

Properties

- perfect fixing on the wall
- secure and easy corner formation
- water-vapour permeable
- moisture resistant
- elastic
- rot-resistant

Composition

- material: PE foam

Substrate

Properties/tests

- The substrate must be dry, level, free of adhesion-reducing residues, dust and grease free as well as fit for the bonding.

Processing

Applying

- Glue edge insulation strips on the substrate and press on firmly. When doing so, ensure they are glued without gaps over the whole area.
- Straight after fixing the edge insulation strip in place, work can be started on fitting the strasser PLAN levelling compound.

Notes

- The edge insulation strip must not be fixed by clamps to the height of the levelling compound.
- Do not cut off the protruding part of the edge insulation strip until the surface covering is laid.
- Store at ambient temperature to avoid warping during application.

Packaging

- 20 m/roll

Storage

- Store dry and as per instructions.
- can be stored in sealed original container/bag for at least 24 months from manufacturing date

Technical Data

Colour	white
Thickness of material	5 mm
Level	50 mm
Length	20 m

All data are average values that were determined under laboratory conditions according to relevant test standards and application tests. Deviations are possible under practical conditions.



General Information

This information sheet provides only general recommendations. If you have any questions when it comes to the actual application, please consult our responsible Technical Sales Adviser or our Service Hotline tel. +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.