

## Reaction accelerator for ÖKOPLAST 1K 20B

### Characteristics

ÖKOPLAST® Plus 55Z is a hydraulically-binding powder which accelerates the drying of the bitumen thick-film coating ÖKOPLAST® 1K 20B.

- Simple handling
- Reactive complete drying
- Optimised range of application

### Use

ÖKOPLAST® Plus 55Z serves to accelerate the drying of ÖKOPLAST® 1K 20B. This makes it possible to work faster under regular conditions or without loss of time under adverse weather conditions.

### Applications:

- Sealing with ÖKOPLAST® 1K 20B

### Specifications

Packaging	Paper sack
Container	2 kg
Mixing ratio	30 l ÖKOPLAST® 1K 20B : 2 kg ÖKOPLAST® Plus 55Z
Delivery form	48 sacks/pal. (6 x 2 kg/ cartons)
Storage	dry, 9 months

### Quantity required

2 kg ÖKOPLAST® Plus 55Z / 30l ÖKOPLAST® 1K 20B

## Application

Add the reaction accelerator **ÖKOPLAST® Plus 55Z** completely to the bitumen thick-film coating **ÖKOPLAST® 1K 20B** and stir in vigorously using a suitable agitator and paddle. The mixing process takes approx. 1 minute and is finished when the mass is homogeneous and free of lumps.

## Important notes

- Comply with the technical data sheet **ÖKOPLAST® 1K 20B**.

## Ingredients

Reactive binder

## Safety provisions/recommendations

All the usual hygiene procedures and precautionary measures for handling chemical products apply. Wear suitable work protection clothing.

## Disposal

The local waste removal regulations must be observed.

## Manufacturer

**Sievert Baustoffe GmbH & Co. KG**  
Mühlenschweg 6, 49090 Osnabrück  
Tel +49 2363 5663-0, Fax +49 2363 5663-90  
hahne-bautenschutz.de, info-hahne@sievert.de

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply. Version as of 12.2020