



WALL AND FLOOR DESIGN

NSTB Natural stone carpet floor binder

ready to use binder for quick-mix natural stone carpet



PROPERTIES

- solvent-free

APPLICATIONS

- a lightfast and abrasion resistant floor coating is created by mixing it with quick-mix NST natural stone carpet
- applicable on concrete floors, screeds and floor tiles
- in the floor area
- for interior and external use

SUBSTRATE

Usable on concrete floors, screeds and floor tiles.

The substrate must be dry, firm, load-bearing, dimensionally stable, clean and free of adhesion-reducing contamination.

Pre-treat absorbent substrates beforehand with quick-mix natural stone carpet floor primer. In the case of non-absorbent substrates such as old tile coverings, carry out a scratch filling with quick-mix natural stone carpet seal.

PROCESSING

Do not use or allow to harden in air, material or substrate temperatures of less than +10°C, in the case of expected night time frost or at temperatures of over +30°C, in direct sunlight, extremely heated substrates and/or in strong wind.

Pour the entire contents into the bucket of quick-mix natural stone carpet and mix intensively using a slowly rotating mixer.

Coarsely distribute the mix in a layer thickness of 8 mm over the prepared substrate with a squeegee and then compact it with a smoothing trowel.

The processing time is about 75 minutes.

Protect against moisture until completely dry.

After about 8 hours, the floor surface can be walked on carefully; after about 2 days it is fully hardened and load-bearing.

Clean tools and equipment with thinner immediately after use.

CONSUMPTION

consumption: 1 kg for approx. 20 kg NST Natural stone carpet (approx. 1,75 m²)

STORAGE

Store dry and as per instructions.

PACKAGING

- 1 kg/can

DISPOSAL

Due to the Green Dot, the empty packaging can be disposed of via the Dual System Germany.

NOTE

The usual hygiene and precautionary measures when handling chemical products must be observed. Wear suitable protective clothing.

Follow further instructions in the safety data sheet.



WALL AND FLOOR DESIGN

NSTB Natural stone carpet floor binder

ready to use binder for quick-mix natural stone carpet

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.

29.01.2023

EMERGENCY NUMBER: +49 551 19 240

quick-mix is a Sievert brand
Sievert Baustoffe SE & Co. KG
Mühlenschweg 6 • 49090 Osnabrück • Phone +49 541 601-01 • Fax +49 541 601-853 • info@quick-mix.de • www.quick-mix.de