


akurit GEP

Diagonal reinforcement arrow

diagonal reinforcement on opening corners for crack prevention

- alkali resistant
- mesh size: approx. 4 × 4 mm
- weight: approx. 165 g/m²



Applications

- for minimizing/avoiding tension cracks
- as additional reinforcement in the area of windows and doors (corners)

Properties

- high tensile strength
- alkali-resistant, slip-proof textile glass scrim
- quick and easy processing

Processing

Applying / Processing / Assembling

- Fill mesh moulded part going out diagonally with AKURIT adhesive and reinforcement mortar into the window and door opening.
- Then apply the ETICS surface reinforcement.

Notes

- For reveal depths > 15 cm, insert reinforcement mesh into the reveal in addition.

Packaging

- 100 pcs/carton

Storage

- Store dry and as per instructions.

General notes

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.