

IMBERAL DB-PV 89ZH



Sealing tape polypropylen-fleece

Characteristics

IMBERAL® DB-PV 89ZH is a special sealing tape made of transversely elastic and longitudinally stable polypropylene fleece. The **IMBERAL® DB-PV 89ZH** is fleece-laminated on both sides for optimum adhesion.

- waterproof
- highly elastic
- fleece-laminated
- high adhesion to the surface sealing
- water-, weather- and alkali-resistant

Use

IMBERAL® DB-PV 89ZH is used for bridging movement and component joints as well as the flexible and waterproof formation of edge and connection joints on walls and floors, indoors, outdoors and in wet areas. Furthermore, it is used for the integration of built-in parts made of wood, plastic and metal in connection with FPD sealing.

Fields of Application

- interior and exterior
- movement joints
- connection joints
- connections
- plinth waterproofing

Specifications

Roll	20 m
Width	120 mm, 250 mm, 500 mm
Thickness	0.6 mm (+/- 0.1 mm)
Colour	grey
Inner corner* Delivery form	60 × 60 × 120 mm 25 pieces/carton
Outer corner* Delivery form	60 × 60 × 120 mm 25 pieces/carton
Storage	frost-free, 24 months

Quantity required

per running meter	1 m
* carton only	

IMBERAL DB-PV 89ZH

Preparation of the surface

The substrate must be prepared according to the specifications in the technical data sheet of the waterproofing and/or bonding material to be used. As a rule, the substrate must be load-bearing and free of dust, dirt and other adhesion-reducing substances.

Application

Apply the selected waterproofing material as a contact layer and work in the joint tape over the entire surface without leaving any bubbles. Then rework with the respective waterproofing material.

hahne system products

PROLASTIC® 55Z
IMBERAL® RSB 55Z
IMBERAL® 2K 20B
IMBERAL® 2K-D 20B
IMBERAL® 2K Winter 26B
IMBERAL® S100 90B
INTRASIT® DSM-Pro 54Z
INTRASIT® Poly-C1 54Z
ÖKOPLAST® 1K 20B
ÖKOPLAST® 2K 20B

Important notes

- Work the sealing tape into expansion and movement joints in loops
- Observe the processing instructions of the respective waterproofing product used.

Safety provisions/recommendations

no particular measures necessary.

Disposal

The local waste removal regulations must be observed.

Manufacturer

Sievert Baustoffe GmbH & Co. KG
Mühlenschweg 6, 49090 Osnabrück
Tel. +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply.
Version as of 9.2021