KSE

Lime film remover



Ready-made cleaner

■ colour: colourless



APPLICATIONS

- for removal of lime and cement films on concrete and masonry surfaces
- for removing bloom and light dirt
- for the removal of concrete and masonry residue
- on all ceramic materials, such as wall and flooring tiles, mosaic, split tiles. Porphyry, etc.
- not suitable for materials sensitive to acids such as marble or limestone
- for external and interior use

PROPERTIES

- solvent-free
- acid-free
- inorganicready for use

PROCESSING

Temperature	The product is ready for use.Do not dilute.		
Mixing / Preparation / Processing	 Must be pre-wet when using in masonry construction. Spray the contaminated concrete or masonry surface with KSE lime film remover, e.g. use a fruit tree spraying device with an extended pipe. When the spray is applied, the light areas start to "foam". It may be necessary to apply the spray several times until the stains are completely dissolved. The effect of KSE lime film remover can be helped by a scrubbing brush or mechanical action. Rinse with clean water. 		
Applying	■ Clean all tools and equipment with water immediately after use.		
Cleaning the tools	Areas not made of concrete, precast concrete components, washed concrete slabs, plasters, screeds, clinker bricks and other ceramic substrates must be covered.		

PACKAGING

- 11.8 l/canister
- 30 l/canister

STORAGE

■ Store in the original, unopened packaging in dry, frost-free conditions.

KSE

Lime film remover



QUANTITY REQUIRED / YIELD

■ consumption: approx. 150 - 350 ml/m² depending on application method

SAFETY AND DISPOSAL INSTRUCTIONS

- If any product gets into the eyes, rinse out immediately with clean tap water. Consult optician. Clean with plenty of water after skin contact.
- Wash off splashes that get onto clothing immediately with clean water.
- Follow further instructions in the safety data sheet.

Disposal

- Completely empty and recycle the packaging.
- Dispose of the material in accordance with the official regulations.

GENERAL INFORMATION

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.