akurit PUR-FIX W58

Friction bearing profile

two-section plastic profile with integrated PUR sealing tape

 compression movement absorption up to 4 mm, shear up to 2 mm





Applications

 for decoupling in WDVS in the case of buildings with different materials (e.g. raising solid structures with wood)

Properties

- · Plastic profile produced according to DIN 16941
- UV and weather resistant

Processing

Applying / Processing / Assembling

- · Install insulation according to ETICS approval.
- The joint must be adapted to the slide bearing profile (joint height 10 mm).
- Slide the profile between the insulation and, if necessary, fix it in the insulation with plastic nails.
- Install plaster system according to ETICS approval.
- Finally, pull off the protective tab and remove the red activation tab.

Storage

- · Store dry, flat and frost-free.
- Deformation of the product due to improper storage must be avoided.

Packaging

5 pcs/carton

Technical Data

Length

2.0 m

All data are average values that were determined under laboratory conditions according to relevant test standards and application tests. Deviations are possible under practical conditions.

General notes

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.

