



WALL AND FLOOR DESIGN

NSTG Natural stone carpet floor primer

primer for using quick-mix NST Natural stone carpet in floor areas



TECHNICAL INFORMATION

pH value approx. 11

Colour transparent

All data are average values that were determined under laboratory conditions according to relevant test standards and application tests. Deviations are possible under practical conditions.

PROPERTIES

- solvent-free
- ready-to-use

APPLICATIONS

- strengthens as primer the building material surface and forms a stable base for following layers
- in the floor area
- for interior and external use

SUBSTRATE

In the case of non-absorbent substrates, carry out a scratch filling with quick-mix natural stone carpet seal in advance.

PROCESSING

Do not use or allow to harden in air, material or substrate temperatures of less than +10°C, in the case of expected night time frost or at temperatures of over +30°C, in direct sunlight, extremely heated substrates and/or in strong wind.

Shake well in original container before use.

Apply thinly and undiluted to the substrate by brushing, rolling or spraying. Enables easy processing and rapid work progress.

Apply the following covering only to the dried primer.

Clean all tools and equipment with water immediately after use.

Carefully cover adjacent surfaces and components (e.g. windows, window sills, etc.). Wash off contamination immediately with water.

CONSUMPTION

consumption: 750 ml for approx. 3,0 m²

STORAGE

Store in the original, unopened packaging in dry, frost-free conditions.

PACKAGING

- 750 ml/cup

DISPOSAL

Due to the Green Dot, the empty packaging can be disposed of via the Dual System Germany.

NOTE

The usual hygiene and precautionary measures when handling chemical products must be observed. Wear suitable protective clothing.

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.

29.01.2023



WALL AND FLOOR DESIGN

NSTG Natural stone carpet floor primer

primer for using quick-mix NST Natural stone carpet in floor areas

EMERGENCY NUMBER: +49 551 19 240

quick-mix is a Sievert brand
Sievert Baustoffe SE & Co. KG
Mühlenschweg 6 • 49090 Osnabrück • Phone +49 541 601-01 • Fax +49 541 601-853 • info@quick-mix.de • www.quick-mix.de