



Low-solvent, bituminous primer

- active period:
approx. 2 hours at +20°C
approx. 1 day at -5°C



APPLICATIONS

- to improve adhesion especially of
BD2KW 2K winter bituminous thick coating
- for priming and adhesion promotion on extruded polystyrene hard foam boards
- for external and interior use

PROPERTIES

- ready for use
- can be stored and processed down to -5 °C
- rollable and spreadable
- dust-binding

SUBSTRATE

Properties/tests	<ul style="list-style-type: none"> ■ The substrate must be dry, load-bearing, clean, dust-free and free of adhesion-reducing residues, release agents, efflorescence and sintered coatings. ■ Plasters must be hardened.
Pretreatment	<ul style="list-style-type: none"> ■ Remove loose particles, dust and adhesion-depleting contaminants.

PROCESSING

Temperature	<ul style="list-style-type: none"> ■ Processable at air, material and substrate temperatures from -5 °C to +35 °C.
Applying	<ul style="list-style-type: none"> ■ ÖKOTAN special bitumen primer can be brushed or rolled on. The primer is applied undiluted at temperatures from -5 °C to 0 °C. At temperatures > 0 °C, ÖKOTAN special bitumen primer can be diluted with water in a ratio of 1:1.
Drying / Hardening	<ul style="list-style-type: none"> ■ The primer must be protected against adverse weather conditions. ■ The subsequent coating may not be applied until completely dry.

PACKAGING

- 5 kg/bucket
- 25 kg/bucket



STORAGE

- Store dry and as per instructions.
- Storage temperature: > -5 °C

QUANTITY REQUIRED / YIELD

- consumption: approx. 150 g/m²

TECHNICAL DATA

Crack bridging class

Rain resistance after approx. 2 hours

Drying time at least 3 days

Temperature resistance, permanent -20°C to +100°C

All data are average values that were determined under laboratory conditions according to relevant test standards and application tests. Deviations are possible under practical conditions.

SAFETY AND DISPOSAL INSTRUCTIONS

Safety ■ Follow further instructions in the safety data sheet.

Disposal ■ Completely empty and recycle the packaging.
■ Dispose of the material in accordance with the official regulations.

GENERAL INFORMATION

This information sheet provides only general recommendations. Should you have any queries relating to a specific application, please contact our technical sales advisor or call our hotline: +49 541 601-601. The technical data refer to + 20 ° C and 60% relative humidity. All of the details given are based on our current knowledge and experience and on the assumption that the materials are professionally applied and used for their normal purpose. All of the details are non-binding and do not release users from their duty to undertake their own tests to ensure suitability for the intended application. Due to the effects of different weather, processing and construction site conditions, no guarantee can be given for the general validity of all details. We reserve the right to make changes as a result of further development of the product and applications engineering. The general rules for construction engineering, the valid standards and guidelines, and the technical working guidelines must be observed. The publication of this technical data sheet renders all previous editions of this data sheet void. Please obtain the latest information from our website.