

Solvent mixture/Thinner for solvent-containing products

Characteristics

HADALAN® EPV 38L is a universally usable solvent mixture.

Use

HADALAN® EPV 38L for dissolving impurities, for viscosity adjustment of PU systems as well as for cleaning tools.

Areas of application:

- Polyurethane and epoxy resin products
- HADALAN®- and DAKORIT® products

Specifications

Packaging	Metal canisters
Barrel	10 l
Delivery form	75 barrels/pallet
Density	0.89 kg/l
Storage	approx. 24 months

Quantity required

Depending on application

Application

The cleaning of processing equipment as well as solvent-resistant substrates can be done with **HADALAN® EPV 38L**, provided the material to be removed has not yet hardened completely. For dilution, **HADALAN® EPV 38L** is added to the material to be thinned while stirring constantly. The quantity is given in the respective data sheet.

Important notes

- If used indoors, ensure sufficient cross-ventilation.
- Contains flammable solvent.
- Use suitable protective gloves, protective eyewear and protection from sprays.

Ingredients

Organic solvents

Safety provisions/recommendations

Information regarding the safety during transport, storage and handling are included in the updated safety data sheet.

Disposal

The local waste removal regulations must be observed.

Manufacturer

Sievert Baustoffe GmbH & Co. KG
Mühlenschweg 6, 49090 Osnabrück
Tel +49 2363 5663-0, Fax +49 2363 5663-90
hahne-bautenschutz.de, info-hahne@sievert.de

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply.
Version as of 12.2020