



WALL AND FLOOR DESIGN

NST Natural stone carpet

natural stone graining for quick-mix natural stone carpet



PROPERTIES

- Grain size: 2 – 4 mm
- The natural stone grains are artificially rounded, washed and dried and thus allow particularly easy processing. All natural stone grains are completely dyed through, colour-fast and weather-resistant.
- quick-mix natural stone carpet is available in six different colours.

APPLICATIONS

- a lightfast and abrasion resistant coating is created by mixing it with natural stone floor or wall binder
- not for permanently wet areas (e.g. showers)
- for walls and floors
- for interior and external use

SUBSTRATE

The substrate must be firm, load-bearing, dry and free from dust and other adhesion-reducing substances. With increased air humidity, there is a risk that condensation will form on the substrate. This water film must be completely dried.

Level uneven substrates beforehand.

PROCESSING

For processing as a floor covering, mix the contents with quick-mix natural stone carpet floor binder using a slowly rotating mixer. As a wall covering, mix the contents completely with quick-mix natural stone carpet solid wall and quick-mix natural stone carpet wall binder.

For larger areas, use buckets from a single batch number if possible. In case of different batch numbers, mix the contents of the buckets together so that there are no partial colour differences.

Clean all tools and equipment with water immediately after use.

Carefully cover adjacent surfaces and components (e.g. windows, window sills, etc.). Wash off contamination immediately with water.

CONSUMPTION

consumption: 20 kg for approx. 1,75 m²

STORAGE

Store dry and as per instructions.

PACKAGING

- 20 kg/bucket

DISPOSAL

Completely empty and recycle the packaging.

NOTE

The usual hygiene and precautionary measures when handling chemical products must be observed. Wear suitable protective clothing.

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.

29.01.2023

WALL AND FLOOR DESIGN

NST Natural stone carpet

natural stone graining for quick-mix natural stone carpet

EMERGENCY NUMBER: +49 551 19 240

quick-mix is a Sievert brand
Sievert Baustoffe SE & Co. KG
Mühlenschweg 6 • 49090 Osnabrück • Phone +49 541 601-01 • Fax +49 541 601-853 • info@quick-mix.de • www.quick-mix.de