



WALL AND FLOOR DESIGN

NSTW Natural stone carpet wall binder

ready to use binder for quick-mix natural stone carpet



PROPERTIES

- solvent-free

APPLICATIONS

- a lightfast and abrasion resistant wall coating is created by mixing it with quick-mix NST natural stone carpet
- strengthens as primer the building material surface and forms a stable base for following layers
- also usable as primer
- in the wall area
- for interior and external use

SUBSTRATE

Suitable for substrates such as concrete, plastering mortar, gypsum plaster, aerated concrete or similar

The substrate must be dry, firm, load-bearing, dimensionally stable, clean and free of adhesion-reducing contamination.

Level uneven substrates beforehand.

PROCESSING

Do not use or allow to harden in air, material or substrate temperatures of less than +10°C, in the case of expected night time frost or at temperatures of over +30°C, in direct sunlight, extremely heated substrates and/or in strong wind.

For use as a primer, place 0.5 kg in a clean bucket and apply thinly to the substrate using a brush/roller. Apply only as much binder as can be processed with quick-mix natural stone carpet until the onset of skin formation. For use as a binder, pour the remaining 2.5 kg into the 20 kg bucket of quick-mix natural stone carpet and mix intensively using a slowly rotating mixer. Application always in conjunction with quick-mix natural stone carpet solid wall. With the smoothing trowel, work the mix in a layer thickness of approx. 8 mm wet-in-wet into the previously applied primer, distribute evenly and smooth.

The processing time is about 60 minutes.

Protect against moisture until completely dry.

Clean all tools and equipment with water immediately after use.

Carefully cover adjacent surfaces and components (e.g. windows, window sills, etc.). Wash off contamination immediately with water. Not suitable for permanently wet areas.

CONSUMPTION

consumption:

primer: 0,5 kg for approx. 1,75 m²

binder: 2,5 kg for approx. 1,75 m²

STORAGE

Store in the original, unopened packaging in dry, frost-free conditions.

PACKAGING

- 3 kg/bucket

DISPOSAL

Due to the Green Dot, the empty packaging can be disposed of via the Dual System Germany.



WALL AND FLOOR DESIGN

NSTW Natural stone carpet wall binder

ready to use binder for quick-mix natural stone carpet

NOTE

The usual hygiene and precautionary measures when handling chemical products must be observed. Wear suitable protective clothing.

The statements are made based on extensive tests and practical experiences. They cannot be applied to every application case. Therefore, we recommend carrying out application trials if necessary. Subject to technical changes in the course of further development. Furthermore, our General Terms and Conditions of Business apply.

29.01.2023

EMERGENCY NUMBER: +49 551 19 240

quick-mix is a Sievert brand
Sievert Baustoffe SE & Co. KG
Mühlenschweg 6 • 49090 Osnabrück • Phone +49 541 601-01 • Fax +49 541 601-853 • info@quick-mix.de • www.quick-mix.de