HADALAN® ColourChips 89\

HADALAN® ColourChips 89V



Colour chips for decorative surface designing

Characteristics

HADALAN® ColourChips 89V are light-resistant, coloured decorative chips for making appealing ground coverings.

- Light-resistant
- · Colour-fast
- Easy to process

Use

HADALAN® ColourChips 89V are used in conjunction with the respective HADALAN® coating product for creating decorative surface protection systems for both indoors and outdoors.

Areas of application:

- · Balcony and terrace surfaces
- · Floor surfaces, indoors
- Tiling
- Mineral substrates

Specifications

Packaging Cardboard boxes

Barrel 1 kg
Colour tones Mix grey-white

White light grey dark grey black cream brick-red pigeon blue tobacco Bicolor grey Bicolor anthracite Bicolor cappuccino

Bicolor vanilla

Grain size 2 - 8 mm Storage dry, 24 months

Quantity required

Depending on application 0.08 - 0.3 kg/m²

Contrast scattering depending on

desired layout 0.05 - 0.15 kg/m² whole-area scattering 0.25 - 0.3 kg/m²

HADALAN® ColourChips 89V



Preparation of the surface

The substrate must have load bearing capacity, be dry on the surface and free of dirt, dust, cleaning agent residues or other separating substances. In case of significant temperature changes, in conjunction with increased atmospheric humidity, there is a danger of condensate water formation on the surface of the substrate. Before starting the coating work, this water film should have dried completely.

Application

- 1. HADALAN® ColourChips 89V are scattered in a previously applied adhesive layer while still wet.
- The scattering for interspersing can be done by hand, or with a scattering cup or a Chiron blower.
- After complete hardening, a transparent final sealing is required.
- 4. Further details can be obtained from the respective technical codes of practice or the processing instructions "Renovating, coating and decorative design with HADALAN® PUR liquid plastics.

hahne system products

HADALAN® PUR Top 32P HADALAN® Topcoat M 12P HADALAN® PUR Top 32P transparent HADALAN® EPV 38L HADALAN® VS 12E HADALAN® VS-E 12E HADALAN® LF41 12E HADALAN® LF51 12E

Important notes

- Follow the processing instructions or the technical codes of practice of the respective system products.
- HADALAN® ColourChips 89V should be protected from moisture during the processing. Store dry.

Ingredients

Polymer colour chips

Safety provisions/recommendations

No special measures required.

Disposal

The local waste removal regulations must be observed.

Manufacturer

Sievert Baustoffe GmbH & Co. KG Mühleneschweg 6, 49090 Osnabrück Tel +49 2363 5663-0, Fax +49 2363 5663-90 hahne-bautenschutz.de, info-hahne@sievert.de This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply. Version as of 12.2020